



Temperature range: **+1°C/+10°C**

Refrigerating unit: **External**

Refrigerant/Cooling factor: **R134a / R290**

Name	LUZON 3.75-mod/C	LUZON 3.13-mod/C	LUZON 2.50-mod/C	LUZON 1.88-mod/C	LUZON 1.56-mod/C	LUZON 1.25-mod/C	LUZON 0.94-mod/C
Code	BA280-c	BA270-c	BA260-c	BA250-c	BA240-c	BA230-c	BA220-c
Length [mm]	3750	3125	2500	1875	1563	1250	938
Height [mm]	1230+/-10	1230+/-10	1230+/-10	1230+/-10	1230+/-10	1230+/-10	1230+/-10
Depth [mm]	1180	1180	1180	1180	1180	1180	1180
Capacity [dm ³]	729	609	486	366	303	243	183
Display area [m ²]	2,9	2,4	1,9	1,4	1,2	1	0,7
Total Display Area (TDA) [m ²]	-	-	-	-	-	-	-
Temp. range [°C]	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)
Temp. class	-	-	-	-	-	-	-
Climate class	-	-	-	-	-	-	-
Energy efficiency class	-	-	-	-	-	-	-
Refrigerant	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449	R134a / R290	R134a / R290	R134a / R290	R134a / R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	14	17	22	26	34	43	51

Standard equipment

device without side panels prepared for multiplexing (MOD/A)

powered only by external aggregate

device prepared for multiplexing

static cooling

body with service – side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of white coated steel

storage chamber back doors – hinged (not applicable to corners)

worktop – stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

straight front glass pane (which can slightly be opened)
LED lamp (color of choice: white, confectionery or meaty "deep pink")
bumper - different colors available (IGLOO pattern book)
automatic defrost
electronic temperature controller with digital display (IGLOO)

Options

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)
wooden sides + glass sides - selectable colour (IGLOO colour chart)
housing with base panel from staff side made of stainless steel
front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)
front panel color - different colors available (IGLOO pattern book)
custom front panel color (after consultation with the IGLOO Sales Department)
base panel made of stainless steel
display space with coloured sheet - selectable colour (IGLOO colour chart)
storage chamber made of stainless steel
exposition area made of acid resistant stainless steel
storage chamber made of acid - resistant stainless steel
exposition area - stepped - 2 steps
exposition area - stepped - 3 steps
powder painted evaporator
night blinds made of plexi glass
worktop - granite grey (thickness - 20 mm)
worktop - granite Balmoral (thickness : 20 mm)
worktop - granite black (thickness : 20 mm)
additional exposition glass shelf
fans enforcing air circulation
additional LED light in top lamp profile
automatic defrost
device with temperature range from -2 °C to +4 °C (includes electric defroster heaters)
analog thermometer
electronic temperature recorder + software
temperature recorder wire
socket with fuse
customer front shelf (aluminum profile anodised color silver or gold)
front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart) (excludes the buffer)
movable partition (low ,glass on stands , placed in exposition area)
top fixed partiton (high , glass in exposition area)
bottom fixed partition (made from stainless steel in storage chamber)
fixed insulated partition panel (increases the module length by 30mm)
runner for small movable table
small movable table for scale or cash register (400x500mm)

