



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Name	SANTIAGO NWS
Code	SA107
Length [mm]	1380
Height [mm]	1225+/10
Depth [mm]	1190
Capacity [dm ³]	150
Display area [m ²]	0,9
Total Display Area (TDA) [m ²]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	-
Climate class	-
Energy efficiency class	D
Refrigerant	R134a / R290
Rated voltage [V]	230/50Hz
Rated power [W]	242

Standard equipment

internal cooling aggregate

static cooling

external housing made of white coated steel (from the stuff side)

base and front panel made of colored coated steel - different colors available (Igloo pattern book)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of stainless steel

storage chamber back doors - hinged

grey granite worktop (thickness 20 mm)

anodised aluminum profiles color gold or silver (IGLOO pattern book)

front glass - telescopic lifting system

night blinds made of plexi glass

lamp with LED light (meat color)

bumper - different colors available (IGLOO pattern book)

insulated ABS side panels - different colors available (IGLOO pattern book) - thickness : 40 mm

device leveling legs
 automatic defrost
 condenser outlet to container
 electronic temperature controller with digital display (IGLOO)
 condenser impurity or fan operation failure alarm

Options

external housing made of stainless steel (from staff side)
 front panel color - different colors available (IGLOO pattern book)
 base color - different colors available (IGLOO pattern book)
 exposition area - stepped - 2 steps
 exposition area - stepped - 3 steps
 exposition area made of acid resistant stainless steel
 storage chamber made of acid - resistant stainless steel
 powder painted evaporator
 worktop - granite Balmoral (thickness : 20 mm)
 worktop - granite black (thickness : 20 mm)
 worktop - stainless steel
 LED light (confectionary color)
 additional exposition glass shelf
 set of wheels (castors)
 device with temperature range from - 2 °C to +4 °C
 automatic condenser vaporization
 additional temperatur regulator
 electronic temperature recorder + software
 temperature recorder wire (RS232 - USB)
 movable partition (low ,glass on stands , placed in exposition area)
 top fixed partiton (high , glass in exposition area)
 fixed partition (high, glass in exposition area ; stinless steel in storage chamber)



