



Temperature range: **3H1(+1/+10°C)**

Refrigerating unit: **External**

Refrigerant/Cooling factor: **R448A / R449A / R452A / R407C / R407A / R407F / R407H / R134A**

	Tobago 3/1.25-mod/C	Tobago 3/1.88-mod/C	Tobago 3/2.50-mod/C	Tobago 3/3.75-mod/C	Tobago 3/HEAD-mod/C
Code	TB330.DP	TB350.DP	TB360.DP	TB380.DP	TB300E.DP
Length [mm]	1250	1875	2500	3750	1875
Height [mm]	1515+/-15	1515+/-15	1515+/-15	1515+/-15	1515+/-15
Depth [mm]	950	950	950	950	950
Capacity [dm <sup>3</sup> ]	-	-	-	-	-
Display area [m <sup>2</sup> ]	-	-	-	-	-
Total Display Area (TDA) [m <sup>2</sup> ]	1,37	2,09	2,79	4,21	2,64
Temp. range [°C]	(+2 ± +10°C)	(+2 ± +10°C)	(+2 ± +10°C)	(+2 ± +10°C)	(+2 ± +10°C)
Temp. class	3M1/3M2/3H1	3M1/3M2/3H1	3M1/3M2/3H1	3M1/3M2/3H1	3M1/3M2/3H1
Climate class	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )	3 ( 25°C ; 60% RH )
Energy efficiency class	C	D	D	D	C
Refrigerant	R448A / R449A / R450A / R407F / R404A / R507	R448A / R449A / R450A / R407F / R404A / R507	R448A / R449A / R450A / R407F / R404A / R507	R448A / R449A / R450A / R407F / R404A / R507	R448A / R449A / R450A / R407F / R404A / R507
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	597	942	994	1301	942

## Standard equipment

powered only by external aggregate

device prepared for multiplexing

dynamic cooling (ventilated)

ecological polyurethane foam insulation

base and front panel made of white coated steel (contact the Igloo sales department)

front bottom panel made of coated steel - different colors available (Igloo pattern book)

cokół dolny z uszczelką przypodłogową

interior and exposition shelves made of coated steel - different colors available (Igloo pattern book)

exposition shelves with height and angle adjustment

price stripes - different colors available (IGLOO pattern book)

górne oświetlenie LED (do wyboru barwa światła- biała, cukiernicza lub mięsna)

electronic temperature controller with digital display

mechanical expansion valve

siphoned condensate drain - diameter of the connector pipe  $\varnothing$  40

## Options

boki zespolone szklane

boki zespolone szklane z lustrem po wewnętrznej stronie

custom colors of top front panel

custom bottom front panel colour (after consultation with the Igloo sales department)

device interior and exposition shelves made of stainless steel

device interior and exposition shelves made of acid - resistant stainless steel

additional shelf illumination - LED light

good securing fence

drzwi przesuwne z szybami zespolonymi (TOBAGO 3 DP) - zapytaj o dostępność

display space thermometer

no thermostat - 2 x temperature sensor NTC [10k $\Omega$ ]

odszywanie parownika grzałkami elektrycznymi \*\*\*

elektroniczny zawór rozprężny z regulatorem sterującym (Carel / Danfoss)

