



automatic defrost

electronic temperature controller with digital display (IGLOO)

## Options

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

wooden sides + glass sides - selectable colour (IGLOO colour chart)

device without side panels prepared for multiplexing (MOD/A)

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid - resistant stainless steel

exposition area - stepped - 2 steps

exposition area - stepped - 3 steps

powder painted evaporator

worktop - granite Balmoral (thickness : 20 mm)

worktop - granite black (thickness : 20 mm)

worktop - stainless steel

additional exposition glass shelf

fans enforcing air circulation

additional LED light in top lamp profile

automatic defrost

the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)

analog thermometer

electronic temperature recorder + software

temperature recorder wire

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart) (excludes the buffer)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

fixed insulated partition panel (increases the module length by 30mm)

runner for small movable table

small movable table for scale or cash register (400x500mm)

