



Temperature range: **+1°C/+10°C**

Refrigerating unit: **External**

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Name	SANTIAGO NZW-MOD/C
Code	SA106W-c
Length [mm]	1380
Height [mm]	1225+/10
Depth [mm]	1190
Capacity [dm ³]	170
Display area [m ²]	1,1
Total Display Area (TDA) [m ²]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	-
Climate class	-
Energy efficiency class	D
Refrigerant	R134a / R290
Rated voltage [V]	230/50Hz
Rated power [W]	29

Standard equipment

powered only by external aggregate

device prepared for multiplexing

dynamic cooling (ventilated)

external housing made of white coated steel (from the stuff side)

base and front panel made of colored coated steel - different colors available (Igloo pattern book)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of stainless steel

grey granite worktop (thickness 20 mm)

anodised aluminum profiles color gold or silver (IGLOO pattern book)

front glass - telescopic lifting system

night blinds made of plexi glass

lamp with LED light (meat color)

bumper - different colors available (IGLOO pattern book)

device leveling legs

automatic defrost

electronic temperature controller with digital display (IGLOO)

Options

external housing made of stainless steel (from staff side)

front panel color - different colors available (IGLOO pattern book)

base color - different colors available (IGLOO pattern book)

exposition area - stepped - 2 steps

exposition area - stepped - 3 steps

additional exposition glass shelf

exposition area made of acid resistant stainless steel

storage chamber made of acid - resistant stainless steel

powder painted evaporator

worktop - granite Balmoral (thickness : 20 mm)

worktop - granite black (thickness : 20 mm)

worktop - stainless steel

LED light (confectionary color)

additional temperatur regulator

electronic temperature recorder + software

temperature recorder wire (RS232 - USB)

customer front shelf (aluminum profile anodised color silver or gold)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

fixed partition (high, glass in exposition area ; stinless steel in storage chamber)

insulated ABS side panels - different colors available (IGLOO pattern book) - thickness : 40 mm

