



Temperature range: **+1°C/+10°C**

Refrigerating unit:

Refrigerant/Cooling factor: **R134a / R290**

Name	JOLA 700.1 GASTRO
Code	JO100.1/GASTRO
Length [mm]	700
Height [mm]	2000 +/-10
Depth [mm]	880
Capacity [dm ³]	700
Display area [m ²]	2,1
Total Display Area (TDA) [m ²]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	-
Climate class	-
Energy efficiency class	C
Refrigerant	R134a / R290
Rated voltage [V]	230/50Hz
Rated power [W]	414

Standard equipment

internal cooling aggregate placed on the bottom

dynamic cooling (ventilated)

external housing made of coated steel - different colors available (Igloo pattern book)

interior made of stainless steel

hinged doors with combined glass – choice of door opening direction

ecological polyurethane foam insulation

internal frame with guides adapted for GN 1/1 containers

5 pcs of plastified reticulated strengthened shelves, with height and angle adjustment

price stripes – different colors available (IGLOO pattern book)

top panel illuminated with LED light – different plexiglass colors available (IGLOO pattern book)

automatic defrost

condenser outlet to container

single vertical interior lighting – LED light

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

external housing color – different colors available (IGLOO pattern book)

external housing made of stainless steel

interior made of acid resistant steel

hinged doors self – closer

door lock with key

fan stopping switch

chrome reticulated strengthened shelves

additional plastified reticulated shelf + set of rails

additional chrome reticulated strengthened shelf + set of rails

internal top and side illumination – LED lights

gastronomic container GN 1/1 – depth 40 mm

gastronomic container GN 1/1 – depth 100 mm

device with temperature range from -6 °C to 0 °C

automatic condenser vaporization

electronic temperature recorder + software

temperature recorder wire

SMS alarm module + temperature recorder with emergency power supply

USB-MGSM TTL wire for SMS module programming

JOLA 700.1 GASTRO



