



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Name	KING 1.0 DP AT	KING 1.3 DP AT	KING 1.6 DP AT	KING 1.9 DP AT	KING 2.5 DP AT
Code	KG100DP-AT	KG101DP-AT	KG102DP-AT	KG103DP-AT	KG104DP-AT
Length [mm]	1000	1310	1610	1920	2540
Height [mm]	2170+/10	2170+/10	2170+/10	2170+/10	2170+/10
Depth [mm]	890	890	890	890	890
Capacity [dm <sup>3</sup> ]	748	966	1208	1449	1944
Display area [m <sup>2</sup> ]	3,1	4,2	5,2	6,3	8,4
Total Display Area (TDA) [m <sup>2</sup> ]	-	-	-	-	-
Temp. range [°C]	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)	(+1 ± +10°C)
Temp. class	-	-	-	-	-
Climate class	-	-	-	-	-
Energy efficiency class	C	C	C	C	D
Refrigerant	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	687	904	909	1170	1486

## Standard equipment

energy efficient cooling aggregate HITACHI placed on the back of the device

dynamic cooling (ventilated)

ecological polyurethane foam insulation

top and bottom front panel made of white coated steel

top panel illuminated with LED light - different plexiglass colors available (IGLOO pattern book)

interior and exposition shelves made of white coated steel

exposition shelves with height and angle adjustment

price stripes - different colors available (IGLOO pattern book)

automatic condensate pump (up to 0,6m height)

internal side illumination - LED lights (white color)

self - closing sliding doors with combined glass

device leveling legs

automatic defrost

electronic temperature controller with digital display (IGLOO)



