



Temperature range:

Refrigerating unit:

Refrigerant/Cooling factor:

Name	CUBE 2 BAKE 0.6N 1400	CUBE 2 BAKE 0.9N 1400	CUBE 2 BAKE 1.3N 1400	CUBE 2 BAKE 0.6N 1200	CUBE 2 BAKE 0.9N 1200	CUBE 2 BAKE 1.3N 1200
Code	CU203.3NB	CU202.3NB	CU201.3NB	CU203.2NB	CU202.2NB	CU201.2NB
Length [mm]	640	940	1340	640	940	1340
Height [mm]	1400±10	1400±10	1400±10	1400±10	1400±10	1400±10
Depth [mm]	845	845	845	845	845	845
Capacity [dm <sup>3</sup> ]	104	155	225	104	155	225
Display area [m <sup>2</sup> ]	0,6	0,9	1,3	0,6	0,9	1,3
Total Display Area (TDA) [m <sup>2</sup> ]-	-	-	-	-	-	-
Temp. range [°C]	-	-	-	-	-	-
Temp. class	-	-	-	-	-	-
Climate class	-	-	-	-	-	-
Energy efficiency class	-	-	-	-	-	-
Refrigerant	-	-	-	-	-	-
Rated voltage [V]	-	-	-	-	-	-
Rated power [W]	-	-	-	-	-	-

## Standard equipment

ambient device without cooling system and possibility of installing it

external glass elements made of insulating glass with argon filling and silkscreen black, white or gray screen, RAL 7042 print

wooden melamine front panel - different colors available (IGLOO pattern book)

internal frame painted - different colors available (IGLOO pattern book)

wooden rack

stainless crumb trays

bakery tray rack 400x600 (0.6 - 6 pcs.; 0.9 - 6 pcs.; 1.3 - 12 pcs.)

socket with fuse

glass exposition shelves with height and angle adjustment placed on the frame

back sliding doors with combined glass (Cube 2 0.6 - hinged doors with choice of door opening direction)

kick plinth made of painted steel (IGLOO pattern book)

bottom housing made of melamine (wood) - different colors available (IGLOO pattern book)

top internal LED illumination front frame LED illumination

## Options

device prepared for multiplexing

internal frame made of stainless steel (does not apply to aluminum shelf frame)

kick plinth made of stainless steel

additional shelf illumination - LED light

set of wheels (castors)

