



Temperature range: **+1°C/+10°C**

Refrigerating unit:

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Name	OLA 1400.4
Code	OL100.4
Length [mm]	1635
Height [mm]	2000 +/10
Depth [mm]	800
Capacity [dm ³]	1400
Display area [m ²]	4,4
Total Display Area (TDA) [m ²]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	-
Climate class	-
Energy efficiency class	C
Refrigerant	R404a / R507 / R448 / R449
Rated voltage [V]	230/50Hz
Rated power [W]	809

Standard equipment

internal cooling aggregate placed on the bottom

dynamic cooling (ventilated)

external housing made of coated steel - different colors available (Igloo pattern book)

internal housing made of white coated steel

ecological polyurethane foam insulation

hinged doors with combined glass

back wall with combined glass

10 pcs of plastified reticulated shelves, with position adjustment

price stripes - different colors available (IGLOO pattern book)

top panel illuminated with LED light - different plexiglass colors available (IGLOO pattern book)

device leveling legs

automatic defrost

codenser outlet to container

internal side illumination - LED lights (white color)

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

static cooling

external housing color - different colors available (IGLOO pattern book)

external housing made of stainless steel

internal housing made of stainless steel

horizontally divided doors

self - closing sliding doors

hinged doors self - closer

door lock with key

fan stopping switch

plastified strengthened shelves

chrome reticulated shelves

chrome strengthened reticulated shelves

additional plastified reticulated shelf + handle set

additional plastified reticulated strengthened shelf + handle set

additional chrome reticulated shelf + handle set

additional chrome reticulated strengthened shelf + handle set

additional interior illumination - LED light (white color)

device with temperature range from -6 °C to 0 °C

automatic condenser vaporization

electronic temperature recorder + software

temperature recorder wire (RS232 - USB)

SMS alarm module + temperature recorder with emergency power supply

USB - MGSM TTL wire for SMS module programming

OLA 1400.4

