



Temperature range: **+1°C/+10°C**

Refrigerating unit:

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Name	OLA 1400.2 AG
Code	OL100.2/AG
Length [mm]	1635
Height [mm]	2035 +/-10
Depth [mm]	800
Capacity [dm <sup>3</sup> ]	1400
Display area [m <sup>2</sup> ]	4,4
Total Display Area (TDA) [m <sup>2</sup> ]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	-
Climate class	-
Energy efficiency class	C
Refrigerant	R404a / R507 / R448 / R449
Rated voltage [V]	230/50Hz
Rated power [W]	703

## Standard equipment

internal cooling aggregate placed on the top

dynamic cooling (ventilated)

external housing made of coated steel - different colors available (Igloo pattern book)

interior made of white coated steel

hinged doors with combined glass

ecological polyurethane foam insulation

10 pcs ( 5 levels ) of plastified reticulated shelves, with height adjustment + bottom base shelf

price stripes - different colors available (IGLOO pattern book)

top panel illuminated with LED light - different plexiglass colors available (IGLOO pattern book)

automatic defrost

condenser outlet to container

double upper LED illumination

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

## Options

external housing color – different colors available (IGLOO pattern book)

---

external housing made of stainless steel

---

interior made of stainless steel

---

fixed stainless steel partition panel (not tight)

---

horizontally divided doors

---

hinged doors self – closer

---

door lock with key

---

fan stopping switch

---

plastified strengthened shelves

---

chrome reticulated shelves

---

chrome strengthened reticulated shelves

---

additional plastified reticulated shelf + handle set

---

additional plastified reticulated strengthened shelf + handle set

---

additional chrome reticulated shelf + handle set

---

additional chrome reticulated strengthened shelf + handle set

---

internal rack with 18 drawers (9 levels) in stainless steel (excludes interior lighting)

---

automatic condenser vaporization

---

device with temperature range from -6 °C to 0 °C

---

electronic temperature recorder + software

---

temperature recorder wire

---

SMS alarm module + temperature recorder with emergency power supply

---

USB-MGSM TTL wire for SMS module programming

---

# OLA 1400.2 AG

