



Temperature range: -18°C/-12°C

EWA 500.1 M
EW100.1M
660
2035 +/10
760
500
1,4
-
(-18 ± -12°C)
-
-
C
R404a / R507 / R448 / R449
230/50Hz
602

Standard equipment

internal freezing aggregate placed on the bottom

dynamic cooling (ventilated)

external housing made of coated steel - different colors available (Igloo pattern book)

interior made of white coated steel

self - closing hinged doors with heated combined glass - choice of door opening direction

ecological polyurethane foam insulation

hinged doors self - closer

heated door frame

5 pcs of plastified reticulated shelves, with height adjustment + lower base shelf

price stripes - different colors available (IGLOO pattern book)

top panel illuminated with LED light – different plexiglass colors available (IGLOO pattern book)

automatic defrost



automatic condenser vaporization	
single vertical interior lighting – LED light	
fan stopping switch	
electronic temperature controller with digital display (IGLOO)	
condenser impurity or fan operation failure alarm	

Options

external housing color - different colors available (IGLOO pattern book)

external housing made of stainless steel

interior made of stainless steel

door lock with key

plastified strengthened shelves

chrome reticulated shelves

chrome strengthened reticulated shelves

additional plastified reticulated shelf + handle set

additional plastified reticulated strengthened shelf + handle set

additional chrome reticulated shelf + handle set

additional chrome reticulated strengthened shelf + handle set

internal top and side illumination – LED lights

electronic temperature recorder + software

temperature recorder wire

SMS alarm module + temperature recorder with emergency power supply

USB-MGSM TTL wire for SMS module programming



EWA 500.1 M



