



Temperature range: **+2°C/+8°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404a / R507 / R448 / R449**

Name	JUMBO 1.25	JUMBO 1.88	JUMBO 2.50	JUMBO 3.75
Code	JMB130	JMB150	JMB160	JMB180
Length [mm]	1350	1975	2600	3850
Height [mm]	1235+/-10	1235+/-10	1235+/-10	1235+/-10
Depth [mm]	1205	1205	1205	1205
Capacity [dm ³]	400	600	800	1200
Display area [m ²]	0.98	1.48	1.98	2.96
Total Display Area (TDA) [m ²]-	-	-	-	-
Temp. range [°C]	(+2 ± +8°C)	(+2 ± +8°C)	(+2 ± +8°C)	(+2 ± +8°C)
Temp. class	-	-	-	-
Climate class	-	-	-	-
Energy efficiency class	F	F	F	F
Refrigerant	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449	R404a / R507 / R448 / R449
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	548	1042	926	1232

Standard equipment

internal refrigeration unit with innovative low noise HITACHI Scroll compressor

dynamic cooling (2 evaporators)

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

non-threshold storage chamber made of stainless sheets (height 415 mm / 2 x E2 box)

storage chamber back doors - hinged

worktop - stainless steel

silver or gold aluminium profiles

an innovative system for raising the front window

night blinds made of plexi glass

modern LED lighting (lighting colour options: white confectionery, pink)

automatic defrost (electric heaters)

automatic condenser vaporization

electronic temperature controller with digital display (IGLOO)

Options

wooden sides + glass sides - selectable colour (IGLOO colour chart)

device without side panels prepared for multiplexing (MOD/A)

housing with base panel from staff side made of stainless steel

innovative LED lighting (choice of light colour - confectionery, white or meaty)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid - resistant stainless steel

exposition stepped overlay made of stainless steel (1 step)

exposition stepped overlay made of acid resistant stainless steel (1 step)

exposition stepped overlay made of stainless steel (2 step)

exposition stepped overlay made of acid resistant stainless steel (2 step)

powder painted evaporators

worktop - acid-resistant stainless steel

device with temperature range from - 2 °C to +4 °C

display space thermometer

electronic temperature regulator with the registration system (Igloo)

temperature recorder wire

no thermostat - 2 x temperature sensor NTC [10kΩ]

front buffer with stainless steel profile

customer front shelf (aluminum profile anodised color silver or gold)

front shelf for the customer with wooden profiles and stainless steel inserts - selectable colour (IGLOO colour chart)

movable partition (low, glass on stands, placed in exposition area)

fixed partition (high, glass in exposition area stainless steel in storage chamber)

bottom fixed partition (made from stainless steel in storage chamber)

runner for small movable table

small movable table for scale or cash register (400x500mm)

