



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R134a / R290**

Name	SAMOS DEEP NW90
KOD	SA290WG
Length [mm]	1350
Height [mm]	1230+/-10
Depth [mm]	1350
Capacity [dm ³]	78
Display area [m ²]	1,1
Total Display Area (TDA) [m ²]	-
Temp. range [°C]	(+1 ± +10°C)
Temp. class	3H1
Climate class	3 (25°C ; 60% RH)
Energy efficiency class	-
Refrigerant	R290
Rated voltage [V]	230/50Hz
Rated power [W]	314

Standard equipment

insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)

internal cooling aggregate

device prepared for multiplexing

dynamic cooling (ventilated)

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color - coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of stainless steel

storage chamber back doors - hinged (not applicable to corners)

grey granite worktop (thickness 20 mm)

internal frame and aluminum profiles anodised color silver or gold (IGLOO pattern book)

straight side-hung front glass panel (not applicable to corners)

night blinds made of plexi glass

LED lamp (color of choice: white, confectionery or meaty "deep pink")

bumper – different colors available (IGLOO pattern book)
insulated plastic side walls + glass side panels – different colors available (IGLOO pattern book)
automatic defrost
condenser outlet to container
electronic temperature controller with digital display (IGLOO)
condenser impurity or fan operation failure alarm

Options

wooden sides + glass sides – selectable color (IGLOO color guide)
device without side panels prepared for multiplexing (MOD/A)
front glass – telescopic lifting system (not applicable to corners)
housing with base panel from staff side made of stainless steel
front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)
front panel color – different colors available (IGLOO pattern book)
custom front panel color (after consultation with the IGLOO Sales Department)
base panel made of stainless steel
exposition area made of acid resistant stainless steel
storage chamber made of acid – resistant stainless steel
exposition stepped overlay made of stainless steel (1 step)
exposition stepped overlay made of acid resistant stainless steel (1 step)
exposition stepped overlay made of stainless steel (2 step)
exposition stepped overlay made of acid resistant stainless steel (2 step)
powder painted evaporator
worktop – granite Balmoral (thickness : 20 mm)
worktop – granite black (thickness : 20 mm)
worktop – stainless steel
additional exposition glass shelf with illumination – LED light
set of wheels (castors)
automatic defrost
device with temperature range from – 2 °C to +4 °C (includes electric defroster heaters)
automatic condenser vaporization
analog thermometer
electronic temperature recorder + software
temperature recorder wire (RS232 – USB)
front hinged glass electric lock
socket with fuse
customer front shelf (aluminum profile anodised color silver or gold)
front shelf for the customer with wooden profiles and stainless steel inserts – selectable colour (IGLOO colour chart) (excludes the buffer)
movable partition (low ,glass on stands , placed in exposition area)
top fixed partiton (high , glass in exposition area)
bottom fixed partition (made from stainless steel in storage chamber)
fixed insulated partition panel (increases the module length by 30mm)
runner for small movable table
small movable table for scale or cash register (400x500mm)

