



Temperature range: **+2°C/+8°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290**

Name	GASTROLINE PREMIUM EX 1.0GASTROLINE PREMIUM EX 1.5GASTROLINE PREMIUM EX 2.0		
Code	GLP110EX	GLP130EX	GLP140EX
Length [mm]	1000	1500	2000
Height [mm]	1300 ± 10	1300 ± 10	
Depth [mm]	880	880	
Capacity [dm ³]	170	270	365
Display area [m ²]	0,48	0,75	1
Total Display Area (TDA) [m ²]-		-	-
Temp. range [°C]	+2 ÷ +8	+2 ÷ +8	+2 ÷ +8
Temp. class	3H1	3H1	3H1
Climate class	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)	3 (25°C ; 60% RH)
Energy efficiency class	-	-	-
Refrigerant	R290	R290	R290
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	-	-	-

Standard equipment

internal unit	
dynamic cooling (ventilated)	
automatic off-cycle defrosting	
automatic evaporation of condensate	
electronic temperature controller with digital display	IGLOO / CAREL
INOX display area	
PES coated storage area	RAL9010
LED lighting	IGLOO pattern book
AC fans	
powder coated external housing	IGLOO pattern book
granite worktop	grey
front panel made of MELAMINE	IGLOO pattern book
straight front glass	
hinged back doors	
INOX base plinth	

ecological polyurethane foam insulation
audible alarm on the condenser pollution

Options

