



Temperature range: **+30/+60 °C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor:

Name	PROXIMA SLIM HOT OPEN 1.25	PROXIMA SLIM HOT OPEN 1.88	PROXIMA SLIM HOT OPEN 2.50
Code	PRXS100H	PRXS101H	PRXS102H
Length [mm]	1250	1880	2500
Height [mm]	1165+/-10	1165+/-10	1165+/-10
Depth [mm]	970	970	970
Capacity [dm ³]	381	571	761
Display area [m ²]	1,6	2,4	3,2
Total Display Area (TDA) [m ²]-	-	-	-
Temp. range [°C]	(+30 ± +60°C)	(+30 ± +60°C)	(+30 ± +60°C)
Temp. class	-	-	-
Climate class	-	-	-
Energy efficiency class	-	-	-
Refrigerant	-	-	-
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	-	-	-

Standard equipment

lower internal shelf fitted with heating pads, made of stainless steel

stainless heating shelves on a frame with adjustable height and suspension angle

external glass elements made of combined glass with argon filling and black, white or gray RAL7042 silkscreen

front panel with color-coated sheet - selectable color (IGLOO color guide)

base, coloured sheet - selectable colour (IGLOO colour chart)

ecological polyurethane foam insulation

housing with base from staff side made of coated steel - different colors available (Igloo pattern book)

frame and internal back of device made of painted steel - different colors available (Igloo pattern book)

additional illumination of each shelf - T5 LED lights (confectionery color)

electronic temperature controller with digital display (Carel)

Options

lower internal shelf fitted with heating pads, made of acid-resistant steel

exposition shelves on frame ,with height and angle adjustment, made of acid-resistant stainless steel

frame and internal back of device made of stainless steel

frame and internal back of device made of acid-resistant stainless steel

front panel color - different colors available (IGLOO pattern book)

base made of stainless steel

