





Temperature range:

Refrigerating unit:

Refrigerant/Cooling factor:

Name	LADA KAMELEO 0.6	LADA KAMELEO 0.9	LADA KAMELEO 1.3
Code	LS/JA600K	LS/JA900K	LS/JA1300K
Length [mm]	690	990	1390
Height [mm]	920+/10	920+/10	920+/10
Depth [mm]	960 +/5	960 +/5	960 +/5
Capacity [dm3]	-	-	-
Display area [m²]	-	-	-
Total Display Area (TDA) [m²]	-	-	-
Temp. range [°C]	-	-	-
Temp. class	-	-	-
Climate class	-	-	-
Energy efficiency class	-	-	-
Refrigerant	-	-	-
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz
Rated power [W]	14,4	17	34

Standard equipment

front panel and plinth, wooden base - colour selectable (IGLOO colour chart)

small and thin wooden side panels - different colors available (IGLOO pattern book)

glass side panels or combined glass divider for multiplexable devices

curved front glass openable

internal frame painted silver or gold (IGLOO pattern book)

glass display shelf on the rack with adjustable height and suspension angle

bottom shelf made of stainless steel

upper interior lighting + additional illumination of each shelf - LED lights (confectionery color)

socket

single electrical outlet

Options

the device without the wooden sides adapted for serial connection (mod)

additional base plinth - different colors available (IGLOO pattern book)

additional front panel - different colors available (IGLOO pattern book)



additional side panels - different colors available (IGLOO pattern book)

additional thin side panels - different colors available (IGLOO pattern book)

internal frame made of stainless steel for 0.6 model

internal frame made of stainless steel for 0.9 model

internal frame made of stainless steel for 1.3 model

LADA SPRZEDAŻOWA KAMELEO



