



Temperaturbereich: **+30/+60 °C**

Aggregat: **intern**

Kühlmittel:

Name	PROXIMA SLIM HOT OPEN 1.25	PROXIMA SLIM HOT OPEN 1.88	PROXIMA SLIM HOT OPEN 2.50
Code	PRXS100H	PRXS101H	PRXS102H
Länge	1250	1880	2500
Höhe	1165+/-10	1165+/-10	1165+/-10
Tiefe	970	970	970
Volumen	381	571	761
Ausstellungsfläche [m²]	1,6	2,4	3,2
Gesamtanzeigefläche (TDA) [m²]-	-	-	-
Temperaturbereich [°C]	(+30 ± +60°C)	(+30 ± +60°C)	(+30 ± +60°C)
Temp.klasse	-	-	-
Klima-Klasse	-	-	-
Energie-Effizienzklasse	-	-	-
Kältemedium	-	-	-
Verdampfertemperatur	-	-	-
Kälteleistung	-	-	-
Nennleistung	230/50Hz	230/50Hz	230/50Hz
Nennleistung [W]	-	-	-
Energieverbrauch [kWh/24h]	-	-	-

## Standard

lower internal shelf fitted with heating pads, made of stainless steel

stainless heating shelves on a frame with adjustable height and suspension angle

external glass elements made of combined glass with argon filling and black, white or gray RAL7042 silkscreen

Frontpaneel aus beschichtetem Blech in freier Farbe - frei gewählt (Muster IGLOO)

base, coloured sheet - selectable colour (IGLOO colour chart)

Umweltfreundliche Isolierung aus Polyurethanschaum

housing with base from staff side made of coated steel - different colors available (Igloo pattern book)

frame and internal back of device made of painted steel - different colors available (Igloo pattern book)

additional illumination of each shelf - T5 LED lights (confectionery color)

Elektronische Temperaturregelung mit Digital - Display (Carel)

## Optionen

lower internal shelf fitted with heating pads, made of acid-resistant steel

exposition shelves on frame ,with height and angle adjustment, made of acid-resistant stainless steel

frame and internal back of device made of stainless steel

frame and internal back of device made of acid-resistant stainless steel

Frontleiste aus rostfreiem Blech

Unterbau aus rostfreiem Blech

